

Technical Specification

REF: PDI1

ISS: 3

Key Features

- Coloured and Clear lens Options
- 12 or 24 volt operation
- Full Range of ECE Functions
- Uniform Design on all Function
- Compact 55mm Package

Technical Specification

Functions: Direction Indicator

Homologation: ECE

Voltage: 12V | 24V - RD Lamps

Vari-volt (9 -33V) – FD Lamps

Power Consumption : D.I (12V) 1.5W, (24V) 1.5W – RD Lamps

D.I (9-33V) 3.3W – FD Lamps

Connection : Cable 500mm

Fixing : 3 point M4 Screw

IP Rating : IP67

Material : Lens – PMMA | Housing – ABS/Polycarbonate

Temperature Range : -40°C to +85°C

Part Numbers

RD101SZZ-2-2-AA 55mm LED Rear Indicator 12Volt Amber

RD101SZZ-4-2-AA 55mm LED Rear Indicator 24Volt Amber

RD102SZZ-2-2-AA 55mm LED Rear Indicator 12Volt Clear

RD102SZZ-4-2-AA 55mm LED Rear Indicator 24Volt Clear

FD101SZZ-5-2-AA 55mm LED Front Indicator 9-33Volt Amber

FD102SZZ-5-2-AA 55mm LED Front Indicator 9-33Volt Clear

See Also

55mm Fog | Reverse | Stop / Tail

95mm Stop/Tail

122mm Reflex

55mm LED Direction Indicator



Overview

55mm LED lamp, available as: Stop/Tail (combined or individual lamp), Rear Fog, Reverse, Front Direction Indicator Rear Direction Indicator. All Functions are supplied in a compact Package and are available with a clear or coloured lens.

Drawing

